

SHADES

Gypsum Tile

VISIT USGME.COM TO ORDER SAMPLES



FEATURES & BENEFITS

- Laminated Gypsum Ceiling with washable vinyl facing for easy maintenance.
- Available in plain facings with smooth appearance.
- Ultra-high humidity resistant; sag resistance ensures durability in standard or extreme environmental conditions.
- Standard produced with aluminium foil backing which acts as a vapor barrier and resists breathing so panel stays cleaner longer.
- Scrub resistant. Dirt marks are easy to remove.
- Durable, scuff, and scratch resistant for longer life.
- Suitable for areas with high humidity.
- Economical and easy to trim and install.
- Demountable and designed to be installed on the DONN® Brand ceiling suspensions.
- Available in a concealed edge design, specifically produced to elevate the overall space appearance.

APPLICATIONS

- Laboratories
- Commercial retails
- Restrooms and wet areas
- Department stores
- Kitchen, dietary and laundry



PRODUCT
CERTIFIED
FOR
ENVIRONMENTAL
PRODUCT
DECLARATION



CEILING
ATTENUATION
CLASS

TABLE OF PERFORMANCE

Edge Detail	Item	Size (mm)	CAC	Light Reflectance	Anti-Mold & Mildew/Sag Resistance	Fire Rating	Recycled Content	VOC Emission	Cost
SQ 	LG-S6609	600*600*9.5	35	84%			7%	Low	\$
	LG-S2209	610*610*9.5							
	LG-S662	600*600*12.5	40	84%			7%	Low	\$
	LG-S222	610*610*12.5							
	LG-S622	600*1200*12.5	40	84%			7%	Low	\$\$
	LG-S242	610*1220*12.5							
SL 	LG-SR662	600*600*12.5	40	84%			7%	Low	\$\$
	LG-SR222	610*610*12.5							
	LG-SR622	600*1200*12.5	40	84%			7%	Low	\$\$
	LG-SR242	610*1220*12.5							
FL 	LG-SRF662	600*600*12.5	40	84%			7%	Low	\$\$
	LG-SRF222	610*610*12.5							
	LG-SRF622	600*1200*12.5	40	84%			7%	Low	\$\$
	LG-SRF242	610*1220*12.5							
Concealed 	LG-SDC662	600*600*12.5	40	84%			7%	Low	\$\$

GRID PROFILE OPTIONS

DX/DXL SQ Edge	DX/DXL SL Edge	DXT FL Edge	DXF FL Edge	DX/DXL Concealed

SPECIFICATION DETAILS

Shades Gypsum Ceiling Tile meets specifications in accordance with ASTM E1264

Materials Classification

Type: XX,

Pattern: E, G

Substrate and Surface Finish

Gypsum ceiling panel laminated with vinyl-faced

Thickness

9.5mm, 12.5mm

Size

600 x 600mm, 610 x 610mm,

600 x 1200mm, 610 x 1220mm

Edge Detail Trim

Square, Reveal [SL, FL], Concealed [Reveal]

Weight

9.5mm [6.65 kg/m²],

12.5mm [8.75 kg/m²]

Ceiling Attenuation Class [CAC]

[35-40 dB]

Hygiene

Laminate PVC prevents the growth of mold and mildew

Humidity Resistance

Maximum 95% RH / 40°C

Light Reflectance Coefficient [LR]

0.84

Color

White similar to RAL 9003

Surface Burning Characteristics per ASTM E 84

Class A

Thermal Resistance

12.5mm [R 0.45]

Washability / Scrubbability as per ASTM D4828 & D2486

Exceeds 1000 Wash/Scrub Cycles without surface break or the extent of abrasion

Formaldehyde Classification

Class E1 as per EN717-1

Notice: As we are involved in constant products development; this document information is subject to change without prior notice.

Please always refer to usgme.com for the updated products information document.

©2023 **Factory of USG Middle East LTD. Co.** All rights reserved.